

ATLANTIC BULK CARRIERS MANAGEMENT LTD

Principal Particulars

Name of vessel	SPRING JASMINE	Type	BULK CARRIER	Flag	PANAMA
IMO number	9942079	MMSI	352002226	Call sign	3E2218
Build mm/yyyy	01/2023	Yard	TADOTSU SHIPYARD CO., LTD.		
Owners	NISSEN KAIUN CO. LTD.				
Managers	KOWA MARINE INC.				
Classification	NK				
PANDI Club	GARD				

Contact details

Telex	437403154	Email:	master.SPRINGJASMINE@fleetmail.inmarsat.com		
Telephone numbers:	+1-7577021947	+1-7577021941	+870-773063175	Fax:	

Measurement, Dimensions and Cargo capacity

Length Overall	199.98 m	Breadth	32.24 m	GRT	36343
LBP	195 m	Depth	19.30 m	NRT	21151
Summer Draft	13.526 m	Summer DWT	63441 MT	Summer Displ.	75493 MT
Winter Draft	13.245 m	Winter DWT	61715 MT	TPC	61.5 MT/cm
Lightweight	12052 MT	Constant excl BW	241.2 MT	FWA	306.9 mm
Panama Canal GRT / NRT	/ 30086		Suez Canal GRT / NRT	37157.69 / 33890.47	
Bow to H/Coaming # 1	17 m	Height of Center of middle Hold (# 3) from:			
Stern to last H/Coaming	33 m	Water line – light ballast		15.57 m	
Superstructure to last H/Coaming	4 m	Water line – Heavy ballast		12.65 m	
Center of C/H# 1 to center of last hold	126 m	Water line – Fully loaded		7.72 m	
Bow to Bridge	170.6	Stern to bridge	29.3 m	Keel to antenna	47.93 m

Hold Capacities

Hatch covers type : MacGregor Folding type

TOTAL Hold	81115.96 m ³		76683.99 m ³		Hatches Dimension		Dimensions Flat Tanktop	
	Grain	Bale	Length	Breadth	Tank Top stress	Width Fwd	Width Aft	
1	14747.46 m ³	13894.78 m ³	18.40 m	18.72 m	25.17 MT/m ²	11.0 m	23.723.7 m	
2	16726.11 m ³	15802.75 m ³	23.20 m	18.72 m	19.26 MT/m ²	23.7 m	m	
3	16716.25 m ³	15713.94 m ³	23.20 m	18.72 m	25.19 MT/m ²	23.7 m	23.7 m	
4	16742.46 m ³	15811.17 m ³	23.20 m	18.72 m	19.26 MT/m ²	23.7 m	23.7 m	
5	16183.68 m ³	15461.35 m ³	23.20 m	18.72 m	25.17 MT/m ²	23.7 m	14.5 m	
6	m ³	m ³	m	m	MT/m ²	m	m	
7	m ³	m ³	m	m	MT/m ²	m	m	

Strength on main deck 5.19 MT/m² Strength on hatch covers MT/m²

Machinery, Liquid Capacity and Cargo Gear

Main Engine:	MITSUI-MAN B&W 6S50ME-C9.6 2 CYCLE DIESEL ENGINE		Output:	KW 7560	RPM:	99.0
Service speed	14.5 Knots	M/E Consumption	Fully loaded	29.5 MT/day	Ballast	1.5 MT/day
Grade of IFO/MDO that vessel burns:	HSFO / LSMGO			Propeller pitch	m	
Generator Engine set:	3 x	Output:	660 Kw	Emergency Power:	YES4600.8	
In port consumption	With All gear working	4.8 Mt/day	Idle	2.7 Mt/day	Boiler	1.5 Mt/day
Light Ballast capacity	16886.72 m ³	IFO Tanks number	8	Capacity (100%):	2583.02 m ³	
Ballast Hold #	3	16780.47 m ³	MDO Tanks number	3	Capacity (100%):	432.65 m ³
No./ Capacity Ballast pump:	2/900 m ³ /h	Fresh Water Capacity	553.88 m ³	Evaporator:	36 Mt/day	
Cargo gear:	4 cranes, Type: ELECTRO HYDRAULIC Maker: MANABE ZOKI CO., LTD. Capacity 36 MT. Max. Outreach 26 m					
No. of grabs,	4	Type:	TOBU RSHC-150	Maker	TOBU JUKOGYO CO. LTD.	Capacity 15/10/6 M ³

Disclaimer: "Any particulars listed herein are not guaranteed and are not to be used for commercial purposes"